



# Product specifications



Professional range

## **SUPREMIUM<sup>®</sup> DIESEL** (1/1500)

Wynn's Supremium<sup>®</sup> Diesel is an additive package developed to upgrade the quality of regular diesel fuel to premium-grade diesel fuel, especially in filling stations.

### Properties

- ✓ Cetane improver
  - Increases the cetane number of EN 590 diesel fuels by 2 to 4 points.
  - Reduction of NOx and particulates by up to 20%.
  - Reduces fuel consumption by up to 4%.
  - Eases cold starting.
- ✓ Detergency
  - Cleans and keeps clean injectors and fuel system.
  - Maintains and restores optimal engine performance (power).
  - Reduces black exhaust smoke due to an improved combustion.
- ✓ Anti-foam
  - Reduces foam formation by up to 60%.
  - No splashing back of fuel.
  - Quicker and more complete filling-up of the tank (> 15 %).
- ✓ Corrosion inhibitor
  - Prevents rust and corrosion in the injection system.
  - Prevents pitting and wear on fuel system components.
- ✓ Lubricity agent
  - Lubricates and protects fuel pump and injectors.

### Applications

- ✓ Recommended for all diesel engines of vehicles.
- ✓ Also for red diesel fuel (road-construction vehicles, tractors, marine).

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium  
 Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: [mail@wynns.eu](mailto:mail@wynns.eu) – Website: [www.wynns.com](http://www.wynns.com)

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



# Product specifications

## Directions

- ✓ Normal dosage : 0,066 % (1 litre for 1500 litres diesel fuel).
- ✓ If possible use a calibrated dosaging device (on tank lorry or storage tank).

## Packaging

PN 25300 – 1000 l – EN/FR/DE/IT  
PN 25396 – 4X5 l – EN/FR/NL/IT  
PN 25397 – 60 l – EN/FR/IT/RU  
PN 25399 – 200 l – EN/FR/DE/NL

## Note

The storage temperature should not exceed 45°C.

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium  
Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: [mail@wynns.eu](mailto:mail@wynns.eu) – Website: [www.wynns.com](http://www.wynns.com)

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.