



Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

MSDS Version: E04.00

Date of issue: 22/01/2015

Blend Version: 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Ice Proof for Diesel

Product code : W22795

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Diesel fuel additive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.be

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Full text of classification categories and H statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.3; R40
Xn; R65
R43
N; R51/53
R66
R67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazardous ingredients : Mixture of: 2,2',2'',2'''-(ethylenedinitrilotetrakis-N,N-di(C16)alkylacetamide; 2,2',2'',2'''-(ethylenedinitrilotetrakis-N,N-di(C18)alkylacetamide, 2-Butenoic acid,4-oxo-4-(tridecylamino)-, (Z)-, branched, Naphthalene, Hydrocarbons, C10, aromatics, <1% naphthalene

Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways
H317 - May cause an allergic skin reaction
H336 - May cause drowsiness or dizziness

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

EUH phrases	: H351 - Suspected of causing cancer H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: EUH066 - Repeated exposure may cause skin dryness or cracking P102 - Keep out of reach of children P405 - Store locked up P261 - Avoid breathing vapours P280 - Wear protective gloves, protective clothing P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor P302+P352 - IF ON SKIN: Wash with plenty of soap and water P331 - Do NOT induce vomiting P273 - Avoid release to the environment

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% w	Classification according to Directive 67/548/EEC
Hydrocarbons, C10, aromatics, <1% naphthalene	(EC no) 918-811-1 (REACH-no) 01-2119463583-34	>= 90	N; R51/53 Xn; R65 R66 R67
Mixture of: 2,2',2'',2'''-(ethylenedinitrilotetrakis-N,N-di(C16)alkylacetamide; 2,2',2'',2'''-(ethylenedinitrilotetrakis-N,N-di(C18)alkylacetamide	(CAS No) 136920-07-5 (EC no) 406-640-0 (EC index no) 616-047-00-0 (REACH-no) 01-0000015616-68	2,5 - 5	R43
2-Butenoic acid,4-oxo-4-(tridecylamino)-, (Z)-, branched	(CAS No) 84583-68-6 (EC no) 283-219-6 (REACH-no) 01-2119980949-12	1 - 2,5	Xi; R36/38 R43 N; R51/53
Naphthalene	(CAS No) 91-20-3 (EC no) 202-049-5 (EC index no) 601-052-00-2 (REACH-no) 01-2119561346-37	1 - 2,5	Carc.Cat.3; R40 Xn; R22 N; R50/53
oleic acid, compound with N-(2-aminoethyl)ethane-1,2-diamine	(CAS No) 18016-43-8 (EC no) 241-924-6 (REACH-no) 01-2119980026-38	0,1 - 1	Xi; R36/38 N; R51/53

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10, aromatics, <1% naphthalene	(EC no) 918-811-1 (REACH-no) 01-2119463583-34	>= 90	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Mixture of: 2,2',2'',2'''-(ethylenedinitrilotetrakis-N,N-di(C16)alkylacetamide; 2,2',2'',2'''-(ethylenedinitrilotetrakis-N,N-di(C18)alkylacetamide	(CAS No) 136920-07-5 (EC no) 406-640-0 (EC index no) 616-047-00-0 (REACH-no) 01-0000015616-68	2,5 - 5	Skin Sens. 1B, H317
2-Butenoic acid,4-oxo-4-(tridecylamino)-, (Z)-, branched	(CAS No) 84583-68-6 (EC no) 283-219-6 (REACH-no) 01-2119980949-12	1 - 2,5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Naphthalene	(CAS No) 91-20-3 (EC no) 202-049-5 (EC index no) 601-052-00-2 (REACH-no) 01-2119561346-37	1 - 2,5	Carc. 2, H351 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
oleic acid, compound with N-(2-aminoethyl)ethane-1,2-diamine	(CAS No) 18016-43-8 (EC no) 241-924-6 (REACH-no) 01-2119980026-38	0,1 - 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of R- and H-statements: see section 16

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Keep victim at rest in half upright position. Vomiting: prevent asphyxia/aspiration pneumonia. Victim in shock: on his back with legs slightly raised. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. If necessary seek medical advice.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause sensitization by skin contact. skin corrosion/irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
- Symptoms/injuries after ingestion : Headache. Abdominal pain. Harmful if swallowed. May be fatal if swallowed and enters airways. Risk of aspiration pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid. This material can accumulate static charge by flow or agitation and can be ignited by static discharge.
- Explosion hazard : No direct explosion hazard.

5.3. Advice for firefighters

- Firefighting instructions : Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Face-shield. Gloves. protective clothing.
- Emergency procedures : Mark the danger area. Seal off low-lying areas. Large spills/in enclosed spaces: compressed air apparatus. Wash contaminated clothes.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain leaking substance, pump over in suitable containers.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean with detergents. Avoid solvent cleaners.

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Meets the legal requirements. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin. Presents no particular risk when handled in accordance with good occupational hygiene practice.

Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Meets the legal requirements. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place.

Storage temperature : < 45 °C

Storage area : Meets the legal requirements. Keep container tightly closed in a cool, well-ventilated place. Ventilation along the floor.

Special rules on packaging : Keep only in original container. correctly labelled.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Naphthalene (91-20-3)

EU	IOELV TWA (mg/m ³)	50 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
Belgium	Limit value (mg/m ³)	53 mg/m ³
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m ³)	80 mg/m ³
Belgium	Short time value (ppm)	15 ppm
Belgium	Remark (BE)	D

Ice Proof for Diesel

DNEL/DMEL (Workers)

Acute - systemic effects, dermal < mg/kg bodyweight/day

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.

Personal protective equipment : Gloves. Face shield. Safety glasses. Protective clothing.



Hand protection : Neoprene, nitrile. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information : Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear.

Colour : Greenish blue.

Odour : aromatic.

Odour threshold : No data available

pH :

Relative evaporation rate (butylacetate=1) : No data available

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

refraction index	: 1,502
Melting point	: No data available
Freezing point	: < -18 °C
Boiling point	: No data available
Flash point	: 64 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 888 kg/m ³
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 2,53 mm ² /s
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 91,7 %
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful: may cause lung damage if swallowed

Naphthalene (91-20-3)

ATE CLP (oral)	500,000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long lasting harmful effects to aquatic life.
Ecology - water	: Toxic to aquatic life with long lasting effects.

Naphthalene (91-20-3)

LC50 fish 1	6,08 mg/l 96h
-------------	---------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Remove to an authorized waste treatment plant.
--------------------------------	--

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 3082
--------------	--------

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document description (ADR)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics; naphthalene), 9, III, (E)

14.3. Transport hazard class(es)

Class (ADR)	: 9
Danger labels (ADR)	: 9



14.4. Packing group

Packing group (ADR)	: III
---------------------	-------

14.5. Environmental hazards

Dangerous for the environment	:
-------------------------------	---



Other information	: No supplementary information available.
-------------------	---

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010


14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 90

Classification code (ADR) : M6

Orange plates :



Special provisions (ADR) : 274, 335, 375, 601

Transport category (ADR) : 3

Tunnel restriction code (ADR) : E

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E1

EAC code : •3Z

14.6.2. Transport by sea

EmS-No. (1) : F-A, S-F

14.6.3. Air transport

Instruction "cargo" (ICAO) : 964

Instruction "passenger" (ICAO) : 964

Instruction "passenger" - Limited quantities (ICAO) : Y964

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 91,7 %

15.1.2. National regulations

Water hazard class (WGK) : 2 - hazard to waters

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Oral)

Aquatic Acute 1

Aquatic Chronic 1

Aquatic Chronic 2

Asp. Tox. 1

Carc. 2

Eye Irrit. 2

Skin Irrit. 2

Skin Sens. 1

Skin Sens. 1B

Acute toxicity (oral), Category 4

Hazardous to the aquatic environment — Acute Hazard, Category 1

Hazardous to the aquatic environment — Chronic Hazard, Category 1

Hazardous to the aquatic environment — Chronic Hazard, Category 2

Aspiration hazard, Category 1

Carcinogenicity, Category 2

Serious eye damage/eye irritation, Category 2

Skin corrosion/irritation, Category 2

Sensitisation — Skin, Category 1

Sensitisation — Skin, category 1B

Ice Proof for Diesel

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking
R22	Harmful if swallowed
R36/38	Irritating to eyes and skin
R40	Limited evidence of a carcinogenic effect
R43	May cause sensitisation by skin contact
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product